



### GlasKap® CR Cool Roof Cap Sheet

#### Description

GlasKap CR is a white mineral surfaced, white acrylic coated, fiber glass cap sheet for use in built-up roofing systems.

#### Use

GlasKap CR is used as the uppermost finish ply in a variety of built-up roofing systems. The unique surfacing provides protection to the underlying asphalt and membrane, as well as the benefit of a reflective, emissive surface **that meets California Title 24.**

#### Color

GlasKap CR is available in white only.

#### Advantages

- Meets same ASTM as GlasKap
- Same installation as regular GlasKap
- Numerous UL Class A and FM fire approvals
- Should the roof be damaged, repairs are easy to make

JM GlasKap CR meets CA Title 24 under the Standard Prescriptive Approach. For more information, visit [www.jmcoolroofs.com](http://www.jmcoolroofs.com).

#### Typical Physical Properties


**Material meets the requirements of ASTM D 3909.**

#### Sizes

Roll size	1 square (9.29 m <sup>2</sup> )
Roll weight	78 lbs. (35.4 kgs.)
Roll length	36' (11 m)
Roll width	36" (0.92 m)
Rolls per pallet	30
Pallets per truckload	19
Pallet size	.45" (1.14 m) square
Pallet weight	2,375 lbs. (1,077 kgs.)



#### Energy and the Environment

 <b>MEMBER</b> <small>COOL ROOF RATING COUNCIL</small>	Solar Reflectance	Initial 0.76	Weathered Pending
	Thermal Emittance	0.85	Pending
	Rated Product ID	0662-0007	
	Licensed Manufacturer ID	0662	
	Classification	Production Line	
<small>Cool Roof Rating Council ratings are determined for a fixed set of conditions, and may not be appropriate for determining seasonal energy performance. The actual effect of solar reflectance and thermal emittance on building construction may vary.</small>			
<small>Manufacturer of product stipulates that these ratings were determined in accordance with the applicable Cool Roof Rating normal procedures.</small>			

CA Title 24 (CRRC) Compliant	Reflectivity .76	Emissivity .85
LEED	Recycled Content: 0%	SRI 92
Producing Locations: Oklahoma City, OK		

#### Precautions

Refer to the Material Safety Data Sheet and Product Label prior to using this product.

